

KELLY TANKS

CWS ULTRA CONCRETE WASHOUT SYSTEM

The 'Ultra' offers auto pH control (CO₂) and incorporates a high volume pump to supply optimum hose pressure for washoff.

Concrete equipment can be safely washed off onsite. Solids are separated from the wash water and retained within the Adsorption Sack. The remaining water is then continuously recycled and pH is automatically with CO₂.

Closed loop cycle/wash water is recycled

pH can be automatically or manually corrected

Simple to set up, empty and operate

Solids are retained in sack for easy disposal

Dims (mm) approx.	2350 (L) 1640 (W) 1030 (H)
Weight approx.	Unladen: 1080kg Laden: 2080kg
Power Required	110V / 16 Amp
Consumables	Adsorption Sacks pH Neutraliser (optional)
Capacity approx.	1000ltrs

AVAILABLE FOR HIRE OR PURCHASE

1. Use the hose to wash off chute/equipment into Adsorption Sack
2. Water passes through Adsorption Sack, where solids are retained
3. Water is then pumped back into system and automatically neutralised to be re-used indefinitely.

For further information contact
KELLY TANKS on **01889 508944** or
email info@kellytanks.co.uk



01889 508944



www.kellytanks.co.uk



info@kellytanks.co.uk