

KELLY TANKS

CWS CONCRETE WASHOUT SYSTEM

Simple Solutions for washing off concrete wagon chutes and equipment

A cost effective alternative to skips & suction wagons, the CWS allows concrete equipment to be washed off onsite by separating the solids in the wash water and recycling the remaining water. pH can be easily neutralised if required.

Closed loop cycle/wash water is recycled

No hazardous water is generated

Simple to set up, empty and operate

Solids are retained in sack

| | |
|---|---|
| Dims (mm) approx. | 2140 (L) 1560 (W) 1030 (H) |
| Weight approx. | Unladen: 720kg Laden: 1300kg |
| Power Required | 110V |
| Consumables | Adsorption Sacks pH Neutraliser (optional) |
| Capacity approx. | 600ltrs |
| Transport charged at cost – POA 50% deposit required at point of order for purchases Remaining balance required prior to delivery | |

AVAILABLE FOR HIRE OR PURCHASE

1. Use the hose to wash off chute/equipment into Adsorption Sack
2. Water passes through Adsorption Sack, where solids are retained
3. Water is then pumped back into system, to be re-used.

For further information contact
KELLY TANKS on 01889 508944 or
email info@kellytanks.co.uk



01889 508944



www.kellytanks.co.uk



info@kellytanks.co.uk