

CONCRETE ULTRA WASHOUT USER GUIDE

Prior to use

- 1) Kelly Tanks Adsorption Sack should be positioned in Frame. Cover should be on.
- 2) Fill CWS Ultra with approx 1000ltr clean water via Access Cap (located under cover)
If using recycled/washwater to fill system, fill through Adsorption Sack, not via access cap.
- 3) Situate & Connect CO2 Cylinder (c/w Regulator) to Inlet Hose Tail
- 4) Connect **110V/16amp Power supply**, (2.5mm 110V Cable Recommended. Power supply (behind Right hand door) **MIN 3.4 KVA POWER REQUIRED**)
- 5) Turn Isolator to ON Position (behind Left hand door)

IMPORTANT: DO NOT ALLOW WASHWATER TO RUN OVER SIDES OF SACKS OR DIRECTLY INTO BASE
- ALL WASHWATER MUST PASS THROUGH SACK

SYSTEM MUST ONLY BE USED WHEN FITTED WITH A KELLY TANKS ADSORPTION SACK, USING THE SYSTEM WITH NO SACK or ALTERNATIVE SACK WILL CAUSE DAMAGE TO THE SYSTEM AND PUMPS

USING THE WASHOUT

WASHOUT COVER & SACK SHOULD BE IN PLACE AT ALL TIMES WHEN SYSTEM IS IN USE



1. ENSURE POWER SUPPLY IS CONNECTED & ISOLATOR IS IN ON POSITION
2. ENSURE CO2 VAPOUR CYLINDER IS IN SITU AND CONNECTED **USING APPROPRIATE REGULATOR & FITTINGS**
3. ENGAGE AND USE WATER NOZZLE ON HOSE TO WASH OFF EQUIPMENT INTO SACK

AFTER USE - USE HOSE TO RINSE BASE & SUMP OF WASHOUT



WHEN BASE BEGINS TO FILL WITH FILTERED WASH WATER, THE SUBMERSIBLE PUMP WILL KICK IN AND PUMP WASH WATER BACK INTO SYSTEM FOR CONTINUOUS REUSE

Maintenance

- When Sack is $\frac{3}{4}$ filled with solids, remove with forklift and replace with new sack
- Cage and Submersible pump should periodically be removed and base and sump should be cleaned out to keep system clean and running smoothly
- Replace CO2 Cylinder when empty

System should be rinsed and emptied when not in use.

Should system be used for washing grout equipment: when not in use for periods over 2 hours, the entire system **MUST** be rinsed/emptied.

These instructions are to be used as a guide only, if in doubt please refer to user manual or contact the site supervisor.

For further assistance call **01889 508944** or email info@kellytanks.co.uk

KELLY TANKS